fixIteasy

Modular fastening system

Mounts for Philips-monitor

Suitable for Philips monitors:

MX 450, MX 550, MX 600, MX 700, MX 800 MP 30, MP 40, MP 50, X2

In case of order, please specify the type of monitor

ltem-no.	Name	Image Illustrations with Philips Table Top Mount. Not included!			
Mounting on table / Adaption 78338A					
M-5013_B	 B Carrier for Philips monitor adaptable to 78338A to be used with Philips Table Top Mount mount for monitor turnable ±90°, inclinable ±15° with locking lever loading capacity: up to 15 kg 				
Mounting on tal	ble				
M-5100	Carrier for Philips monitor <i>for mounting on table</i> - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 15° - loading capacity: up to 15 kg				
Mounting on de	vices				
M-23397	Carrier for Philips monitor for mounting on devices, (e.g. on Primus anesthetic machine) - to be used with Philips Table Top Mount - mounting over 4 self-locking screws M8 - with counter plate, hole pattern: 80 mm x 80 mm - mount for monitor turnable ± 90°, inclinable ± 15° - loading capacity: up to 15 kg				

ltem-no.	Name	Image Illustrations with Philips Table Top Mount. Not included!		
Mounting on horizontal standard rail 25 x 10 mm				
K-5756_LK	Holder for Philips monitor, long node, for mounting on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 15° - throat depth: 205 mm - loading capacity: up to 15 kg			
K-5756_LK_HST	Holder for Philips monitor, long node, with retaining bar for mounting on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 15° - throat depth: 205 mm - loading capacity: up to 15 kg			
K-5760	Holder for heavy weight Philips monitor for mounting on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 10° - throat depth: 352 mm - loading capacity: up to 15 kg			
K-23410	Small support arm, movable, with cable holder claw, for Philips monitor for mounting on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ± 90°, inclinable ± 15° - with cable holder claw in white - total throat depth: 387 mm - loading capacity: up to 15 kg			
K-23410_S	Small support arm, movable, with long cable holder claw, for Philips monitor for mounting on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ±90°, inclinable ±15° - with long cable holder claw in white - total throat depth: 387 mm - loading capacity: up to 15 kg			

Item-no.	Name	Image Illustrations with Philips Table Top Mount. Not included!		
Mounting on horizontal standard rail 25 x 10 mm				
K-5792	Swivel arm with cable holder claw, for Philips monitor for mounting on standard rail 25 mm x 10 mm - Swivel arm with integrated cable channel, throat depth max.: 450 mm, loading capacity: 8 - 16 kg height adjustment approx.: 350 mm - mount for monitor turnable ± 90°, inclinable ± 15° -with cable holder claw and covers in white - total throat depth: 572 mm - loading capacity: up to 15 kg			
K-5792_S	Swivel arm with long cable holder claw, for Philips monitor for mounting on standard rail 25 mm x 10 mm - Swivel arm with integrated cable channel, throat depth max.: 450 mm, loading capacity: 8 - 16 kg height adjustment approx.: 350 mm - mount for monitor turnable ± 90°, inclinable ± 15° -with long cable holder claw and covers in white - total throat depth: 572 mm - loading capacity: up to 15 kg			
Mounting on w	all or carrier rail			
K-5761	Holder for heavy weight Philips monitor for mounting on wall or carrier rail - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 10° - throat depth: 357 mm - loading capacity: up to 15 kg			
K-23411	Small support arm, movable, with cable holder claw, for Philips monitor <i>for mounting on wall or carrier rail</i> - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ±90°, inclinable ±15° - with cable holder claw in white - total throat depth: 392 mm - loading capacity: up to 15 kg			
K-23411_S	Small support arm, movable, with long cable holder claw, for Philips monitor for mounting on wall or carrier rail - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ±90°, inclinable ±15° - with long cable holder claw in white - total throat depth: 392 mm - loading capacity: up to 15 kg			

ltem-no.	Name	Image Illustrations with Philips Table Top Mount. Not included!			
Mounting on GCX-rail					
K-5763	Holder for heavy weight Philips monitor for mounting on GCX-rail - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 10° - throat depth: 349 mm - loading capacity: up to 15 kg				
K-23413	Small support arm, movable, with cable holder claw, for Philips monitor for mounting on GCX-rail - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ± 90°, inclinable ± 15° - with cable holder claw in white - total throat depth: 384 mm - load capacity: up to 15kg				
к-23413_s	Small support arm, movable, with long cable holder claw, for Philips monitor for mounting on GCX-rail - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ± 90°, inclinable ± 15° - with long cable holder claw in white - total throat depth: 384 mm - loading capacity: up to 15 kg				
Mounting on tube	e d = 36 to 40 mm				
K-5762 – RD38	Holder for heavy weight Philips monitor for mounting on tube d = 36 - 40 mm - to be used with Philips Table Top Mount - mount for monitor turnable ± 90°, inclinable ± 10° - throat depth: 348 mm - loading capacity: up to 15 kg				
K-23422	Small support arm, movable, with cable holder claw, for Philips monitor for mounting on tube d = 36 - 40 mm - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ± 90°, inclinable ± 15° - with cable holder claw in white - total throat depth: 384 mm - load capacity: up to 15kg				
K-23422_S	Small support arm, movable, with long cable holder claw, for Philips monitor for mounting on tube d = 36 - 40 mm - to be used with Philips Table Top Mount - small support arm, casting, with cable channel - mount for monitor turnable ± 90°, inclinable ± 15° - with long cable holder claw in white - total throat depth: 384 mm - load capacity: up to 15kg				

em-no.	Name	Image Illustrations with Philips Table Top Mount. Not included!		
Mobile				
K-23430	 Cart, with carrier rail I = 1500 mm, counterweight, handle and cable holder claw to be used with Philips Table Top Mount base with castors: roller D = 100 mm, free movable, 2 are lockable. width: 370, depth: 480, tare weight: 45 kg, loading capacity: up to 50 kg total height of the rolling carriage: approx. 1700 mm with counterweight 4,375 kg carrier rail with 2 integrated cable channel, I = 1500 mm mount for monitor turnable ± 90°, inclinable ± 15°, throat depth: 210 mm, loading capacity: up to 15 kg with cable holder claw in white 			
K-23430_S	Cart, with carrier rail I = 1500 mm, counterweight, handle and long cable holder claw - to be used with Philips Table Top Mount - base with castors: roller D = 100 mm, free movable, 2 are lockable. width: 370, depth: 480, tare weight: 45 kg, loading capacity: up to 50 kg - total height of the rolling carriage: approx. 1700 mm - with counterweight 4,375 kg - carrier rail with 2 integrated cable channel, I = 1500 mm - mount for monitor turnable ± 90°, inclinable ± 15°, throat depth: 210 mm, loading capacity: up to 15 kg - with long cable holder claw in white			

ltem-no.	Name	Image Illustrations with Philips Table T		
Mobile				
K-21898_H	Cart, antimagnetic design, with wooden pillar and mount for monitor made of stainless steel - wooden column: beechwood, D = 140mm / d = 90 mm - base with castors: antimagnetic, roller D = 100 mm, free movable, 2 are lockable. width: 370, depth: 480, tare weight: 45 kg, loading capacity: up to 50 kg - total height of the rolling carriage: approx. 1300 mm - mount for heavy weight monitor: VESA-Standard 75 / 100 mm, stainless steel, with pipe clamp, inclinable: ± 15°, turnable 360° on the wood column, loading capacity: up to 25 kg, height adjustment via wing nut on the pipe clamp	for monitor with V	ESA interface	
Hooking on bed	Istead or on horizontal standard rail 25x10 mm Carrier for monitor IntelliVue for hooking on bedstead with tube linkage up to D 40 mm or on standard rail 25 mm x 10 mm - to be used with Philips Table Top Mount - W 265 mm x D 260 mm x H 215 mm - loading capacity: up to 12 kg		Illustration: on bedstead Wonitor not included	
M-20284	Carrier for monitor X2 for hooking on bedstead with tube linkage up to D 40 mm or on standard rail 25 mm x 10 mm - W 166 mm x D 200 mm x H 180 mm - with 2x mounting hole Ø 4,4 mm - loading capacity: up to 12 kg		Illustration: on bedstead	

Item-no.	Name	Illustrations with Philips	Image Table Top Mount. Not included!		
Universal mounting					
M-5190	Universal clamp for mounting on: - tubes from d 25 to d 38 mm - standard rail 25 x 10 mm - Pangas rail 35 x 8 mm - turnable ± 90°, inclinable ± 90° - dimensions (without star grip): approx. 60 x74 x34 mm - 2x mounting hole Ø 4,4 mm	for monitor X2			
Optional extras	and cable management				
K-5774	Satellite rack for mounting on standard rail 25 mm x 10 mm or 35 mm x 8 mm - retaining bar: d = 20 mm, length = 195 mm - throat depth: 90 mm - loading capacity: up to 15kg				
K-21545	Cable holder claw on rail fits on standard rail 25 mm x 10 mm or rail 35 mm x 8 mm - colour: white - width: 46 mm (Rail not included)		Illustration: mounted on standard rail		
K-21555	Cable holder claw on rail with star knob clamping fits on standard rail 25 mm x 10 mm - colour: white - width: 46 mm (Rail not included)		Illustration: mounted on standard rail		

M-20262 - 50 WS Cable clip, 50 pieces, white fits on standard rail 25 mm x 10 mm - width: 23 mm. (standard rail not included) Illustration: - from the side - mounted on standard rail M-20262 -100 WS Cable clip, 100 pieces, white fits on standard rail 25 mm x 10 mm - width: 23 mm (standard rail not included) Illustration: - from the side - mounted on standard rail	
M-20262 -100 WS Cable clip, 100 pieces, white fits on standard rail 25 mm x 10 mm - width: 23 mm	